

Nelson's HASK Series connection kits are Factory Mutual and Canadian Standards Association approved for use in Class I, Division 1 hazardous areas when used with approved Nelson heating cables.



HASK-P Power Connection Kit is suitable for connecting one heating cable to customer supplied power wiring.

Kit Contents:

- 1 Approved XP Junction Box, Seal Fitting, Sealing Compound and Packing Fiber
- 1 Aluminum Standoff
- 1 Grommet
- 1 Power Termination with Adhesive Sealant
- 1 3-Point Floating Terminal Block
- 1 Pipe Plug
- 2 Stainless Steel Pipe Clamps (Specify Pipe Size)



HASK-E End Connection Kit is suitable for terminating one heating cable in a CI, D1 heat tracing system.

Kit Contents:

- 1 Approved XP Junction Box, Seal Fitting, Sealing Compound and Packing Fiber
- 1 Aluminum Standoff
- 1 Grommet
- 1 Power Termination with Adhesive Sealant
- 1 3-Point Floating Terminal Block
- 2 Pipe Plugs
- 2 Stainless Steel Pipe Clamps (Specify Pipe Size)



HASK-S Splice Connection Kit is designed for connecting two heating cables in an in-line splice configuration.

Kit Contents:

- 1 Approved XP Junction Box
- 2 Seal Fittings, Reducers, Sealing Compound and Packing Fiber
- 2 Cable Entry Seals with Grommets
- 2 Power Terminations with Adhesive Sealant
- 1 3-Point Floating Terminal Block
- 1 Pipe Plug
- 2 Stainless Steel Pipe Clamps (Specify Pipe Size)



HASK-T Tee Connection Kit is designed for connecting three heating cables in a tee splice configuration.

Kit Contents:

- 1 Approved XP Junction Box
- 3 Seal Fittings, Reducers, Sealing Compound and Packing Fiber
- 3 Cable Entry Seals with Grommets
- 3 Power Terminations with Adhesive Sealant
- 1 3-Point Floating Terminal Block
- 3 Stainless Steel Pipe Clamps (Specify Pipe Size)

Nelsons HASK Series connection kits include all components necessary to complete the installation of Nelsons full line of Class I, Division 1 heat tracing cables. The selection tables below allow for the proper specifying of the complete connection kit assembly (example: HASK - P - 12).

HASK - _____ - _____

| SPECIFY PIPE SIZE | |
|-------------------|-------------|
| 3 | .75 - 2.5 |
| 12 | 3.0 - 10.0 |
| 20 | 12.0 - 20.0 |

| SPECIFY KIT CONFIGURATION | |
|---------------------------|-------------------|
| P | Power Connection |
| E | End Connection |
| S | Splice Connection |
| T | Tee Connection |